

VANDAL-PROOF DOME CAMERA
WITH BUILT-IN IR LED
SK-D105IRD/M943AI



● FEATURES

- True Day&Night function(Exchange of two filters)
- Dual power operation(AC24V&DC12V) with Line-Lock
- Vandal&Fire-poof(UL94, V-O class)
- Weatherproof(IP66)
- Ceiling&Wall mount available
- 20M visible range in total darkness with 22pcs of IR LEDs
- Video test connector for easy installation
- Functions are controllable by the push buttons with semi-OSD

● SPECIFICATION

MODEL	SK-D105IRD/M943AI
CCD TYPE	1/3" COLOR SONY SUPER HAD CCD
PIXELS	410K
RESOLUTION	Color:520TV-LINE, B/W:580TV-LINE
SYNC.TYPE	Internal / External(Line-Lock)
SCANNING	2:1 Interlace
VIDEO OUTPUT	1.0Vp-p (Sync. Negative) Termination 75Ω
r (GAMMA)	r=0.45 typ.
MIN.ILLUMINATION	Color:0.2 Lux/F1.2, 0.002 Lux/F1.2(sens-upX128) B/W:0.09 Lux/F1.2, 0.001 Lux/F1.2(sens-upX128) 0 Lux (20 Range): LED ON
S/N RATIO	50dB or More (AGC OFF)
SHUTTER SPEED	Auto/Manual(X128~1/60(50)~1/120,000s) sens-up&sens-up limit is selectable
POWER SUPPLY	DC 12V & AC24V Dual Voltage
DIGITAL ZOOM	ON/OFF Selectable(X1~X8)
WHITE BALANCE	ATW/AWC/Manual (1,800°K~10,500°K)
CURRENT CONSUMPTION	MAX.500mA(at DC12V,AC24V)LED ON
OSD	Yes
DNR	Low/Middle/High/Off Selectable
SENS-UP	OFF/AUTO (X2~X128)
MIRROR	ON/OFF
MOTION DETECTION	ON/OFF Selectable (4ZONE)
PRIVACY ZONE	ON/OFF Selectable (4ZONE)
DAY&NIGHT	YES
FLICKERLESS	Manual shutter
OPERATION TEMP.	-10℃~50℃
PRESERVATION TEMP.	-20℃~60℃
ACCESSORY BRACKET	SK-AB02, AB03, AB08, AB14
DIMENSION	Ø150 X 95.6(H)mm

● DIMENSIONS

